



AMERICAN MICROSEMICONDUCTOR INC.

P. O. Box 104

Madison, New Jersey 07940 U. S. A.

<http://www.americamicrosemi.com>

[email:sales@americamicrosemi.com](mailto:sales@americamicrosemi.com)

Phone: (973) 377-9566 Fax: (973) 377-3078

Part Number: 1N2927
Manufacturer: American Micro
V(f) @Ipeak (V): 600m
Ipeak Max. (A): .10m
Ipeak Tol. (A): .01m
V(P) (V): 75m
V(V) (V): 475m
Ip/Iv Min.: 2.5
I(F) Max. (A): .50m
r(s) Max. (Ohms): 10
C(t) Max. (F): 80p
T(Oper) Max. (°C): 200

Part Number: 1N2928
Manufacturer: American Micro
V(f) @Ipeak (V): 670m
Ipeak Max. (A): .47m
Ipeak Tol. (A): .05m
V(P) (V): 80m
V(V) (V): 490m
Ip/Iv Min.: 2.5
I(F) Max. (A): 2.5m
r(s) Max. (Ohms): 3.0
C(t) Max. (F): 100p
T(Oper) Max. (°C): 200

Part Number: 1N2929
Manufacturer: American Micro
V(f) @Ipeak (V): 700m
Ipeak Max. (A): 1.0m
Ipeak Tol. (A): .10m
V(P) (V): 80m
V(V) (V): 500m
Ip/Iv Min.: 2.5
I(F) Max. (A): 5.0m
r(s) Max. (Ohms): 2.0
C(t) Max. (F): 150p
T(Oper) Max. (°C): 200

Part Number: 1N2930
Manufacturer: American Micro
V(f) @Ipeak (V): 740m
Ipeak Max. (A): 4.7m
Ipeak Tol. (A): .47m
V(P) (V): 85m
V(V) (V): 520m
Ip/Iv Min.: 2.5
I(F) Max. (A): 15m
r(s) Max. (Ohms): 1.0
C(t) Max. (F): 250p
T(Oper) Max. (°C): 200